



Figure similar

Spare part SIMATIC S7-200, Digital input EM 221, only for S7-22X CPU, 8 DI, 24 V DC, sinking-sourcing

Input current	
from backplane bus 5 V DC, max.	30 mA
Power loss	
Power loss, typ.	2 W
Digital inputs	
Number of digital inputs	8
Source/sink input	Yes
Input voltage	
<ul style="list-style-type: none"> Type of input voltage 	DC
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> for signal "0" 	0 to 5 V
<ul style="list-style-type: none"> for signal "1" 	+15 to +30 V
Input current	
<ul style="list-style-type: none"> for signal "1", typ. 	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	4.5 ms
Cable length	
<ul style="list-style-type: none"> shielded, max. 	500 m
<ul style="list-style-type: none"> unshielded, max. 	300 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> 2-wire sensor 	Yes
— permissible quiescent current (2-wire sensor), max.	1 mA
Potential separation	
Potential separation digital inputs	
<ul style="list-style-type: none"> Potential separation digital inputs 	Yes; Optocoupler
<ul style="list-style-type: none"> between the channels, in groups of 	4
connection method / header	
Plug-in I/O terminals	Yes
Dimensions	
Width	46 mm
Height	80 mm
Depth	62 mm
Weights	
Weight, approx.	150 g
last modified:	3/12/2021

