

\*\*\* spare part \*\*\* SIMATIC S7, TD 200 text display for S7-200, 2-line, with cable (2.5 m) and installation accessories, configuration with STEP 7-Micro/WIN without ATEX approval



Figure similar

General information	
Product type designation	TD 200
Display	
Design of display	LCD backlit
Line display	
<ul style="list-style-type: none"> <li>Number of lines</li> <li>Number of characters per line</li> <li>Character size</li> </ul>	2 20; Characters/line: ASCII, cyrillic; 10 characters/line: Chinese 5 mm
Control elements	
Keyboard fonts	
<ul style="list-style-type: none"> <li>System keys               <ul style="list-style-type: none"> <li>Number of configurable system keys</li> </ul> </li> <li>alphanumeric keyboard</li> </ul>	Yes 9 No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; Power supply via the S7-200 communications interface or optional external power supply unit; the CPU sensor power supply (24 V DC) is not subjected to load
Input current	
Current consumption, max.	120 mA
Interfaces	
Point-to-point connection	
<ul style="list-style-type: none"> <li>Transmission rate, max.</li> </ul>	187.5 kbit/s
1. Interface	
Interface types	
<ul style="list-style-type: none"> <li>RS 485</li> </ul>	Yes
Protocols	
<ul style="list-style-type: none"> <li>PPI               <ul style="list-style-type: none"> <li>Number of nodes, max.</li> </ul> </li> </ul>	Yes 126; S7-200, OP, TP, TBP, PG / PC
Protocols	
AS-Interface	No
Degree and class of protection	
IP (at the front)	IP65
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	0 °C 60 °C
Ambient temperature during storage/transportation	

- min. -40 °C
- max. 70 °C

Dimensions	
Width	148 mm
Height	76 mm
Depth	27 mm
Mounting cutout, width	138 mm
Mounting cutout, height	68 mm
Overall depth	27 mm
Cabinet/switchboard thickness	0.3 mm; 0.3 to 4 mm

Weights	
Weight, approx.	250 g

**last modified:** 3/11/2021 